

# broncolor

*Flash with Dimension*





### Dear Reader

Our company, founded in 1958, with its product brands, broncolor and kobold, has developed over the past half-century into one of the primary solutions for professional lighting systems in the international market. Today we serve three business sectors: professional photography, broadcasting/TV, and events. We chose “50 Light-Years Ahead” as the slogan for our jubilee year in 2008. This statement also reflects our commitment for the future.

The challenge of consistently meeting your needs and repeatedly surprising you with innovations is our motivation – and light our passion. Essentially, we have much in common. Every day and with every new assignment you are challenged to

create different, surprising, more refined images. In this we want to offer you our full support. We take advantage of every personal contact with your colleagues all over the world to ask which solutions would help them meet their daily challenges. The latest innovations from broncolor, which regularly achieve worldwide recognition, grow from these valuable inputs and the untiring efforts of our engineers in pursuit of technological development.

But in parallel with this spirit of innovation, the quality and reliability, that you expect in your daily work in the studio or on location, has lost none of its traditional high importance. Every unit that leaves our production facilities undergoes

exhaustive functional testing. Wherever possible, new developments are made compatible with earlier models. Systematically implemented over the years, this philosophy has enriched the broncolor product line to such an extent that it leaves almost nothing to be desired in terms of operating convenience, long-term value and reliability. And we stand by that.

On our website, [www.broncolor.com](http://www.broncolor.com), you will find detailed information about the entire broncolor product line. Judge for yourself! On the following pages we present the current broncolor product line. We look forward to counting you among our satisfied customers for many years to come.

Jacques Bron



# TABLE OF CONTENTS

---

Company Portrait	6
Technical Concepts	8
broncolor Technologies	11

---

## **The broncolor system**

---

Power Packs	16
Senso Kits	21
Battery Power Packs	22
Move Kits	23
Monolights	24
Siros	26
Kits	28
Lamps	30
Picolite Small Lamp	34
Accessories Picolite Small Lamp	35
Para	36
Para Attachments	39
Reflectors and Attachments	40
Softboxes, Octaboxes and Speedrings	42
Special Reflectors	45
Special Effect Lamps	46
Remote Control	50
Light Shapers in combination with lamps	51
Stands	52
Stand Attachments	53
Flash Tubes, Modelling Lamps and Protecting Glasses	54
Various Bags and Cables	56

---

<b>Gen NEXT</b>	<b>58</b>
<b>Courses</b>	<b>60</b>
<b>Useful Information</b>	<b>62</b>
<b>Rental Service</b>	<b>63</b>

---



### **Creativity is compelling**

In the professional community, the digital image is here to stay. The ability to edit images on computers is now taken for granted. But one factor remains unchanged: light. This factor drives our mission to accompany developments in photography and to advance technological progress in professional lighting. Today, broncolor is the leading brand globally for flash lighting systems, our products can be found in countless studios around the world. Precision, benchmark technology, quality and reliability are

the drivers of this success story. Our headquarters and the technology centre are located in Allschwil near Basel, close to where the German, French and Swiss borders meet. At this globally recognised research triangle, committed broncolor employees forge the future. broncolor is an international brand. Our representatives and service centres are qualified partners for our customers in over 60 countries.

### **The power of innovation**

It is the think tank in which pioneering broncolor technologies were

invented and are continually being refined. Its unfaltering quest for optimisation is based on a constant involvement at the forefront of electrical engineering as well as the identification of new materials and manufacturing processes. The ongoing dialogue with professional photographers and broncolor equipment users also plays an important role. These discussions have often inspired new generations of equipment, safeguarding continuity in an evolution that addresses genuine user needs. The best technical features are worth very little



if they lack operating convenience. For this reason, broncolor also stands for design. Our products are ergonomic, easy to understand, and aesthetically appealing. As people whose perception is quintessentially visual, photographers especially appreciate these attributes.

#### **Quality counts**

Imagine a production day with models, makeup artists, hair stylists, assistants, creative directors, and the client assembled in a studio. Everything is in place, everything is ready. And then, at the decisive moment, the flash system fails: a catastrophe for the client, the agency, and the photographer. Apart from fascination and technical progress, what drives us is the meticulous compliance of every broncolor product with the best standards of quality, precision, and dependability. And these standards are defined by the photographer's expectations. Prior to delivery, every single power pack, every monolight, and each lamp is painstakingly tested for unrestricted functionality and flawless quality. Our two-year factory warranty proves that we stand behind our work. This commitment is globally acknowledged.

#### **The world is our home**

Quality generates acceptance.

The world's most professionally managed studios have embraced broncolor products as the standard for perfect lighting. In return, we emphasise worldwide customer support with more than 100 service centres. In addition to maintenance and repair specialists, every broncolor representative is staffed with competent advisors who can assist photographers in solving lighting problems. At the same time, broncolor's in-house instructors provide training for local service technicians and acquaint them with innovations and new technologies.

In addition to the assurance that they can count on assured support virtually everywhere, photographers also have access to another welcome service at approaching 120 locations around the world: the "broncolor World Light Rental System." broncolor's dedication to quality is also evident by our popular workshops on lighting techniques and the num





### How important are joules for exposure?

To be able to objectively evaluate and compare technical devices, assessment criteria that include technical and economic aspects have to be considered.

The amount of light reaching the CCD chip is important. The parameter J (joules) – also called Ws (watt-seconds) – quantifies the energy content or storage capacity of the flash capacitors. If a flash unit has a storage capacity of 300 joules, it can operate a 300-watt lamp for 1 second or a 300,000-watt lamp for 1/1000 second. The number of joules or watt-seconds gives no information about the actual amount of light that is emitted and that is crucial for lighting purposes, since it ignores certain important factors that can decrease the conversion of electrical energy to light. For example, the flash tube and the unit must be co-ordinated with one another, the reflector must be adapted to the flash tube and the power cable must be dimensioned appropriately. Losses between the flash capacitors and flash tubes, which would otherwise have a negative effect on efficiency, are thereby minimised.

### Guide numbers and f-stops

For amateur and portable flash units, it is common to quote a guide number, which is the product of the f-stop and the distance between the subject and the light source. For example: distance from light source to subject = 2 m, measured f-stop = f/11;  $2 \times 11 = 22$ , and the guide number for that unit is therefore 22. If this value is to serve as a parameter for a flash unit, it must be dependably applicable in every case (i.e. constant). This condition is met only when the light intensity decreases as the square of the distance. This is certainly the case when the light source is small in comparison with the distance between it and the subject, a requirement which flash

units for amateurs fulfill very well, but only seldom flash systems. Their light sources are generally not point-like, but instead are often larger than the subject itself or the distance between the light source and subject. Since in this case the light does not diminish proportionally with the squared distance, the expected f-stop cannot be calculated with this method. For flash systems, therefore, the guide number is a purely theoreti-

cal value and not a usable parameter. broncolor therefore simply quotes the expected f-stop at a distance of 2 meters for its units. The advantage for photographers is that they get a definite statement about exposure that has already taken into account all the losses and efficiencies not accounted for in the energy rating. The figure also allows users to compare the effects of different reflectors.





### Flash units and digital photography

Light quality depends on two factors: first the quality of the light shaper that is used, and second the precision of the flash unit's control system. If the light quantity or light quality of different exposures is not identical, colour shifts are inevitable. broncolor flash systems offer precise control of flash voltage. This outstanding repetitive precision is especially impor-

tant for images using multi-shot cameras. The high-end Scoro A power pack is moreover equipped with broncolor's patented ECTC (Enhanced Colour Temperature Control) technology, which ensures a constant (or deliberately variable) colour temperature over the entire control range.

For users of digital imaging systems who need completely computer-controlled image acquisition,

broncolor offers units that can be remotely radio-controlled from a PC or Macintosh.

 Haze Kware, France





## Innovative Technologies – made in Switzerland

**Innovation as motivation. Although the technologies we have developed are accepted as groundbreaking, they are continuously perfected or further developed. The basis for this is a constant desire to optimise and the continuing study of electrical technologies, new materials and alternative manufacturing processes. Photography is born of light – so it is our mission to accompany its development and to further the advance of technical progress in professional lighting technology.**



FLASH CUT-OFF

### Cut-off technology

Flash duration and light output are the two decisive factors in light control. A microprocessor in Scoro and Move power packs as well as monolights of the Siros S series will calculate for you the shortest or longest flash duration for a given output. This enables rapid flash sequences with up to 50 flashes per second.



CONSTANT COLOUR ECTC

### Constant colour temperature – ECTC

The second generation of our patented ECTC (Enhanced Color Temperature Control) technology, which adapts flash voltage and duration to each other, achieves a constant colour temperature over the entire variation range. With the Scoro S you can change the colour temperature in calibrated steps of + / - 200 K at constant power output.

When multiple lamp heads are connected, constant colour temperature is guaranteed on all channels up to an asymmetry of two f-stops.



CONTROL RANGE

### Individual power distribution

The Scoro S has three lamp outlets, the Scoro E and Move power packs have two each. Each lamp outlet has an individual power controller with LED display, which is adjustable independently of the other outlets. The unit therefore behaves like three (or two) independent power packs. You have a choice of up to 11 f-stops to set the flash output you need. That is a control range from 3 to 3200 J.



SPEED MODE

### Speed Mode

In Speed Mode the charging time and flash duration are reduced by up to 50%, and the maximum flash energy is reduced by 25%. In this way you can achieve up to ten exposures per second at full output, or up to 50 at reduced power. This converts broncolor power packs and monolights with cut-off technology into high performance flash units whenever speed is of the essence. With their active fan cooling, even long series of flashes are no problem.


Speed meets precision – unbeatable flash times



FLASH CUT-OFF

**Cut-off technology**


For consistent flash energy, flash durations can be substantially shorter using broncolor cut-off technology than is possible with conventional units:



t 0.1 = 1/600 s

Why  
t 0.1  
and not  
t 0.5?

**Comparison without broncolor cut-off technology**




t 0.5 does not measure all light relevant for the complete shooting; light is radiated before and after t 0.5, which can result in blurring.



t 0.5 = 1/600 s

**Comparison with broncolor cut-off technology**



The total quantity of light is taken into account.  
No blurring, because the flash is cut off.

**Good to know**

There is no generally valid factor for converting t 0.5 to t 0.1. It is therefore not correct to use t 0.5 to compare different flash durations; for comparisons t 0.1 must be known as well.

## Absolute colour constancy with ECTC\*




CONSTANT COLOUR ECTC

### Constant colour temperature


Patented ECTC technology enables a constant average colour temperature over the entire output range.

**The colour temperature tolerance band is only +/- 50 Kelvin.**


It controls the amplitude of the blue light component according to the warmer red component, which originates at cut-off.





With this unique technology broncolor provides output control over 11 f-stops, or ten f-stop steps, at constant colour temperature. There is no other technology which compares with this performance. With other technologies such a constant colour temperature can only be attained over a maximum of four f-stops. If multiple lamp-heads are connected, the constant colour temperature is guaranteed on all channels with an asymmetry of up to two f-stops.



Even for fast flash sequences, constant colour temperature and quantity of light are the primary quality criteria for broncolor products.



with broncolor technology



without broncolor technology

\*ECTC Enhanced Colour Temperature Control

## Control meets efficiency –enormous control range, individually controllable



### CONTROL RANGE

#### Power distribution

Scoro S units have three lamp outlets, Scoro E and Move have two each. Each lamp outlet has an individual power controller with LED display and is adjustable independently of the other outlets. The unit therefore behaves like three (or two) independent power packs.

The individual power distribution combined with the large control range, at its maximum from 3-3200 Joules, allows the photographer an almost free choice of f-stop.

The required flash output can then be chosen from up to 11 f-stops, or ten f-stop steps. A further power display provides information about the total energy supplied by the power pack. With the buttons beside the display it is possible to change the total energy of all channels simultaneously.



Aperture closed



Aperture open

## Record charging times with Speed Mode



SPEED MODE

### Speed Mode

In Speed Mode, Move can be operated at optimum colour temperature and maximum output with a minimum charging time of 0,9 s (600 J). The Scoro even manages 0,4 s at 1600 J. The shortest charging time is an unbelievable 0,02 s.


How is that possible?

With the Speed button the maximum energy is reduced by 25% and, so, the charging time shortened by up to 50%.

**In this way Move, just like its big brother, the Scoro, achieves the world's shortest charging time of 0,02 s.**

Using this technology stroboscope shootings can be illuminated with only a single flash unit. For example, in technical and scientific photography motion sequences can be made visible.

By alternately triggering several power packs, the number of flashes per second can even be doubled.



with broncolor technology



without broncolor technology



**High-performance flash systems always consist of a separate power pack and one or more lamps. Advantages compared to monolights are the ability to connect several lamps, the big choice of special lamps (e.g. diffused-source lamps, spots, etc.), and the comprehensive range of accessories. The extensive range offers the right solution for every lighting assignment and every budget. Power packs, lamps and accessories from broncolor are, with very few exceptions, also compatible with current monolights, and offer an enormous spectrum of flash energies.**

Scoro, the top model, features individual power distribution, i.e. all lamp outputs can be individually regulated. broncolor's patented ECTC technology (Enhanced Colour Temperature Control) ensures absolute control of colour temperature and flash duration over the entire output range. If multiple lampheads are connected, the constant color temperature is guaranteed on all channels with an asymmetry of up to two f-stops. Numerous additional programmable functions enable widely differing applications. Scoro is the first power pack to incorporate all significant features: Scoro has the fastest charging time, roughly twice as fast as any of the others; Scoro has the shortest flash duration at every output rating.

A Senso power pack is a good introduction to the broncolor system: Senso includes all the features of a studio flash unit in a small volume - ideal when you are on the road. The mains-independent power pack Move 1200 L is notable for its light weight, robustness, and user-friendly plug-in battery. Move is compatible with all broncolor flash units and lamps, and can be used both on location and in the studio.

On all broncolor studio power packs modelling light can be adjusted to be proportional to the differing flash outputs of diverse power packs, and to the number of lamps. In this way the lighting situation can be assessed in the correct relationship to the effective flash output. The robust housing protects the electronics in hard daily use, and the cooling fan and thermostat protect against damage from overheating. Modern micro-processor technology controls the various functions and simultaneously monitors the capacitor and operating modelling-light voltages. With their high-precision regulation of flash voltage, broncolor power packs are ideal for multi-shot digital photography. All models are equipped with a photo-cell and have a large adjustment range in 1/10 f-stop steps. The Senso and Move power packs are equipped with the radio system RFS 2 or RFS 2.1 respectively. For Scoro power packs, there is a choice of RFS or RFS 1. With this radio system, a power pack can be triggered by radio and controlled remotely.





FLASH CUT-OFF



CONSTANT COLOUR ECTC



CONTROL RANGE 11 F-STOPS



SPEED MODE

**Scoro S**

- Ultra-fast flash times down to 1/10'000 s (t 0.1) or 1/14'000 s (t 0.5) thanks to innovative cut-off technology
- Extremely powerful lighting – outputs up to 3200 J
- Three lamp outlets, individually switchable and with fully independent control of each
- ECTC (Enhanced Color Temperature Control) technology for constant colour temperature, and selective colour temperature changing when required
- Long-life halogen modelling light, up to 3 × 650 W and five proportionality stages
- Robust, easily readable 8 cm LED display (240 × 180)
- Elegant, robust metal housing with carbon-look and massive carrying handle
- Speed Mode (Charging time and Flash duration)
- Memory function
- Further special functions, such as alternation, delay and stroboscopic effects



**Scoro 1600 S RFS** | 31.041.XX  
**Scoro 1600 S RFS 2.1** | 31.044.XX

**Scoro 3200 S RFS** | 31.043.XX  
**Scoro 3200 S RFS 2.1** | 31.045.XX

**Normal mode**

Flash energy	1600 J	3200 J
f-stop at 2 m, 100 ISO, reflector P70	64 <sup>2</sup> / <sub>10</sub>	90 <sup>2</sup> / <sub>10</sub>
Flash duration at max. energy* t 0.1 (t 0.5)	1/325 s (1/760 s)	1/160 s (1/390 s)
Variation range for flash duration* t 0.1 (t 0.5)	1/150 – 1/10'000 s (1/450 – 1/14'000 s)	1/85 – 1/10'000 s (1/240 – 1/14'000 s)
Charging time (min. – max. energy) at	230 V	0,02 – 0,6 s
	120 V	0,02 – 1,0 s
	100 V	0,02 – 1,1 s
		Switchable to slow charge
		0,02 – 1,3 s
		0,02 – 2,0 s
		0,02 – 2,2 s
		Switchable to slow charge

**Speed Mode**

Flash energy	1200 J	2400 J
f-stop at 2 m, 100 ISO, reflector P70	45 <sup>9</sup> / <sub>10</sub>	64 <sup>9</sup> / <sub>10</sub>
Flash duration at max. energy* t 0.1 (t 0.5)	1/435 s (1/1'600 s)	1/215 s (1/860 s)
Variation range for flash duration* t 0.1 (t 0.5)	1/150 – 1/10'000 s (1/450 – 1/14'000 s)	1/85 – 1/10'000 s (1/240 – 1/14'000 s)
Charging time (min. – max. energy) at	230 V	0,02 – 0,4 s
	120 V	0,02 – 0,6 s
	100 V	0,02 – 0,7 s
		0,02 – 0,8 s
		0,02 – 1,2 s
		0,02 – 1,4 s

Ready display	Visual and audible (can be switched off), activated when 100% of the selected energy is reached	
Lamp outlets	3 outlets with flash cut-off and ECTC	
Power distribution	Symmetrical and individually asymmetrical	
Control elements	Dust and scratch-resistant, illuminated silicone keypad, setting by radio remote control	
Control range for flash energy	Over 10 f-stops	Over 11 f-stops
Colour temperature	in 1/10 or full f-stop intervals. Choice of joules or percent for LCD display ECTC technology (Enhanced Colour Temperature Control) for constant or specifically adjustable colour temperature	
Modelling light	Halogen max. 3 × 650 W at 200 – 240 V / Halogen max. 3 × 300 W at 100 – 120 V Proportional to flash energy, also full and low settings. Proportionality can be adapted to other broncolor power packs and to monolights	
Additional functions	t 0.1, sequence, delay, interval, colour temperature, alternating, stroboscopic, memory, and many more	
Flash release	Manual release button, photocell, infrared RFS or RFS 2.1 receiver, may be switched off sync cable, IRX 2	
Number of sync sockets	1	1
Computer connection for remote control	1	1
Stabilised flash voltage	+/- 0,3%	
Power requirements	16,0 A (230 V) 15,0 A (120 V) 15,0 A (100 V)	16,0 A (230 V) 15,0 A (120 V) 15,0 A (100 V)
Dimensions without handle	28,8 × 19 × 29,5 cm (11,3 × 7,5 × 11,6")	28,8 × 19 × 40 cm (11,3 × 7,5 × 15,7")
Weight	8,9 kg (19,6 lbs)	12,1 kg (26,7 lbs)

\*Automatic regulation of flash duration and energy for optimum colour temperature. Preselection of minimum flash duration possible



FLASH CUT-OFF  
t 0.1 = 1/8'000 s  
t 0.5 = 1/12'000 s



CONSTANT COLOUR ECTC



CONTROL RANGE

## Scoro E

- Ultra-fast flash times down to 1/8'000 s (t 0.1) or 1/12'000 s (t 0.5) thanks to innovative cut-off technology
- Extremely powerful lighting – outputs up to 3200 J
- Two lamp outlets with individual cut-off and fully independent control of each
- ECTC (Enhanced Color Temperature Control) technology for constant colour temperature of every firing
- Long-life halogen modelling light, up to 3 × 650 W and five proportionality stages
- Robust, easily readable 8 cm LED display (240 × 180)
- Elegant, robust metal housing with carbon-look and massive carrying handle



**Scoro 1600 E RFS** | 31.060.XX  
**Scoro 1600 E RFS 2.1** | 31.062.XX

**Scoro 3200 E RFS** | 31.061.XX  
**Scoro 3200 E RFS 2.1** | 31.063.XX

Flash energy	1600 J	3200 J
f-stop at 2 m, 100 ISO, reflector P70	64 <sup>2</sup> / <sub>10</sub>	90 <sup>2</sup> / <sub>10</sub>
Flash duration at max. energy* t 0.1 (t 0.5)	1/325 s (1/760 s)	1/160 s (1/390 s)
Variation range for flash duration* t 0.1 (t 0.5)	1/265 – 1/8'000 s (1/760 – 1/12'000 s)	1/132 – 1/8'000 s (1/390 – 1/12'000 s)
Charging time (min. – max. energy) at 230 V	0,06 – 1,0 s	0,06 – 1,7 s
	120 V	0,06 – 1,4 s
	100 V	0,06 – 1,5 s
	Switchable to slow charge	Switchable to slow charge

Ready display	Visual and audible (can be switched off), activated when 100% of the selected energy is reached		
Lamp outlets	2 outlets with flash cut-off and ECTC		
Power distribution	Symmetrical and individually asymmetrical		
Control elements	Dust and scratch-resistant, illuminated silicone keypad, setting by radio remote control		
Control range for flash energy	Over 8 f-stops		Over 9 f-stops
	in 1/10 or full f-stop intervals. Choice of joules or percent for LCD display		
Colour temperature	ECTC (Enhanced Color Temperature Control) technology for constant colour temperature		
Modelling light	Halogen max. 2 × 650 W at 200 – 240 V / Halogen max. 2 × 300 W at 100 – 120 V		
	Proportional to flash energy, also full and low settings		
	Proportionality can be adapted to other broncolor power packs and to monolights		
Additional functions	t 0.1, sequence		
Flash release	Manual release button, photocell, RFS or RFS 2.1 receiver, may be switched off, sync cable		
Number of sync sockets	1	1	
Computer connection for remote control	1	1	
Stabilised flash voltage	+/- 0,5%		+/- 0,5%
Power requirements	16.0 A (230 V)	15.0 A (120 V)	15.0 A (100 V)
Dimensions without handle	28,8 × 19 × 29,5 cm (11,3 × 7,5 × 11,6")		28,8 × 19 × 40 cm (11,3 × 7,5 × 15,7")
Weight	8,7 kg (19,2 lbs)		12 kg (26,5 lbs)

\*Automatic regulation of flash duration and energy for optimum colour temperature. Preselection of minimum flash duration possible



### Senso

- High repetitive precision of the colour temperature
- 3 lamp outlets, control over 2 individual channels
- Photocell, infrared and RFS 2 receiver for flash triggering (can be switched off)
- Internal discharge when the power output is reduced
- Slow charge (selectable)
- Front panel, resistant to dust and scratches with illuminated silicone keyboard and LED displays
- Memory function
- Modelling light with two different proportionality levels
- TIPA Award Winner 2011



#### Senso 1200 | 31.050.XX

#### Senso 2400 | 31.051.XX

Flash energy	1200 J	2400 J
f-stop at 2 m (6 ½ ft), 100 ISO,	<b>Litos lamp</b>	<b>Litos lamp</b>
- with Litos reflector	32 <sup>1</sup> / <sub>10</sub>	45 <sup>1</sup> / <sub>10</sub>
- with P70 reflector	45 <sup>8</sup> / <sub>10</sub>	64 <sup>8</sup> / <sub>10</sub>
- with P70 reflector	<b>Pulso G lamp</b>	<b>Pulso G lamp</b>
Flash duration t 0.1 (t 0.5) at 230 V	45 <sup>7</sup> / <sub>10</sub>	64 <sup>7</sup> / <sub>10</sub>
	<b>Litos lamp</b>	<b>Litos lamp</b>
	1200 J: 1/180 s (1/600 s)	2400 J: 1/90 s (1/300 s)
	600 J: 1/360 s (1/1200 s)	1200 J: 1/180 s (1/600 s)
	<b>Pulso G / Unilite lamp</b>	<b>Pulso G / Unilite lamp</b>
	1200 J: 1/100 s (1/300 s)	2400 J: 1/50 s (1/150 s)
	600 J: 1/200 s (1/600 s)	1200 J: 1/100 s (1/300 s)
Charging time (100% of selected energy)	0,4 – 1,5 s (230 V)	0,4 – 2,8 s (230 V)
	0,4 – 1,5 s (120 V)	0,4 – 2,8 s (120 V)
	0,5 – 1,9 s (100 V) 900 J	0,5 – 3,9 s (100 V) 1800 J
Ready display	Visual and audible (can be switched off), signals when 100% of selected energy is reached	
Number of lamp outlets	3	3
Power distribution	Free asymmetry up to 5 f-stops in whole and <sup>1</sup> / <sub>10</sub> f-stop intervals	
Control range of flash energy	7,5 f-stops or 13 J to 1200 J (1 lamp) with activated symmetry switch	
Modelling light	100 – 240 V, halogen max. 3 × 300 W (Litos) 230 V, halogen max. 3 × 650 W (Pulso G / Unilite) Proportional to flash energy, full power	
Flash release	Manual release button, photocell, RFS 2 receiver (radio frequency), sync cable	
Radio (2.4 GHz)	99 workstations, 99 unit addresses, 40 selectable frequency channels	
No. of sync sockets	1	1
Dimensions (L×W×H)	20,3 × 14,8 × 21,8 cm (8 × 5,8 × 8,6") excl. handle	203 × 148 × 300 mm (8 × 5,8 × 11,8"), excl. handle
Weight	4,6 kg (10,1 lbs)	6,9 kg (15,2 lbs)

### Accessories

#### Stand holder Senso

35.117.00





**Senso kit 21**

31.052.XX

includes:

- 1 power pack Senso 1200
- 1 Litos lamp
- 1 Flex 70 x 70 cm (28 x 28")
- 1 sync cable 5 m (16 ft)
- 1 Outdoor trolley backpack

**Senso kit 41**

31.054.XX

includes:

- 1 power pack Senso 2400
- 1 Litos lamp
- 1 Flex 70 x 70 cm (28 x 28")
- 1 sync cable 5 m (16 ft)
- 1 Outdoor trolley backpack

**Senso kit 22**

31.053.XX

Scope of delivery same as Senso kit 21,  
but with 2 Litos lamps

**Senso kit 42**

31.055.XX

Scope of delivery same as Senso kit 41,  
but with 2 Litos lamps



FLASH CUT-OFF  
t0.1 = 1/10'000 s  
t0.5 = 1/14'000 s



CONSTANT COLOUR ECTC  
5500 K



CONTROL RANGE  
9 F-STOPS



SPEED MODE  
0.02s



## Move 1200 L

(including protective bag, plug-in lithium battery and charger)

- Super-fast flash durations up to 1/8'500 s (t 0.1) or 1/20'000 s (t 0.5) thanks to innovative cut-off technology
- Outputs up to 1200 J
- Two lamp outlets with individual cut-off and fully independent control of each
- ECTC (Enhanced Color Temperature Control) technology for constant colour temperature
- Speed Mode (Charging time and Flash duration)
- Eco operation for more flashes per battery charge (up to 230 flashes at full power)
- Unbelievably small, light and compact
- Robust housing with eight "protective rubber bumpers"
- Variable operating-period limits for modelling light



### Move 1200 L | 31.016.XX

Flash energy	1200 J
f-stop at 2 m (6 ½ ft), 100 ISO, P70 reflector	64 1/10 (with MobiLED)
Flash duration t0.1 (t0.5)	fastest: 1/8'500 s (1/20'000 s) max. energy: 1/350 s (1/1000 s)
Charging time (for 100% of selected energy)	0,02 – 1,9 s (Speed Mode 0,02 – 0,9 s)
No. of flashes per battery charge	approx. 170 / 230 (Eco-Mode) at 1200 J approx. 50'000 at 4 J
Lamp outlets	2 outlets with flash cut-off and ECTC
Power distribution	Symmetrical and individually asymmetrical
Controls	illuminated silicone keyboard, resistant to dust/scratches, LCD display
Flash energy control range	9 f-stops in 1/10 or full f-stop intervals Display in joules or percent (4,5 – 1200 J)
Modelling light	Max. 2 × halogen 100 W or 2 × LED 30 W charge selectable switch-off time setting (10/30/60 s) Operatig in continuous light mode over 2 hours
Colour temperature	ECTC technology (Enhanced Colour Temperature Control) for constant colour temperature
Flash triggering	Manual release button, photocell, RFS 2.1, sync cable
Radio release	outdoors up to 50 m (164 ft) (possible range up to 300 m / 984 ft) indoors up to 30 m (98 ft) (possible range up to 300 m / 984 ft)
Dimensions (L×W×H) excl. handle	21 × 17 × 23 cm (8,3 × 6,7 × 9")
Weight of power pack	6,2 kg (13,7 lbs)
Lithium battery	14,4 V / 6,6 AH Li-FePo4 with integrated battery status
Accessories	outdoor trolley backpack (S.23), weatherproofed power pack soft case, rechargeable battery, battery recharger, continuous light adapter



**Move Outdoor kit 1**

31.026.XX

includes:

- 1 power pack Move 1200 (incl. battery)
- 1 MobiLED lamp
- 1 Softbox Flex 70 × 70 cm (28 × 28")
- 1 RFS 2 transmitter kit
- 1 battery recharger
- 1 sync cable
- 1 adapter cable
- 1 continuous light adapter
- 1 weatherproofed Move soft case
- 1 outdoor trolley backpack



**Move Outdoor kit 2**

31.027.XX

includes:

- 1 power pack Move 1200 L (incl. battery)
- 2 MobiLED lamps
- 1 Softbox Flex 70 × 70 cm (28 × 28")
- 1 umbrella 85 cm
- 1 RFS 2 transmitter kit
- 1 battery recharger
- 1 sync cable
- 1 adapter cable
- 1 continuous light adapter
- 1 weatherproofed Move soft case
- 1 outdoor trolley backpack



**Outdoor Para kit**

31.028.XX

includes:

- 1 power pack Move 1200 L (inkl. battery)
- 1 MobiLED lamp
- 1 Para 88 P kit
- 1 RFS 2 transmitter kit
- 1 battery recharger
- 1 sync cable
- 1 adapter cable
- 1 continuous light adapter
- 1 weatherproofed Move soft case
- 1 outdoor trolley backpack



**Accessories**

**Weatherproofed Move soft case**

36.520.00

Weight: 0.2 kg (0.4 lbs)

Dimensions [L × W × H]:

21 × 14 × 7 cm (8.2 × 5.5 × 2.7 ")



**Outdoor trolley backpack**

36.519.00

Weight: 5 kg (11 lbs)

Dimensions [L × W × H]:

56 × 41 × 27 cm (22 × 16.1 × 10.6 ")



**Battery recharger**

36.151.00



**Lithium battery**


36.152.00



**Continuous light adapter**

36.129.00

Dimensions: 30.8 × 18.5 × 22.9 cm (12.1 × 7.2 × 9 ")



**Move battery bag**

36.552.00

Weight: 0.2 kg (0.4 lbs)

Dimensions [L × W × H]:

21 × 14 × 7 cm (8.2 × 5.5 × 2.7 ")



## Siros

**The new Siros monolight is pure innovation. A little light giant with infinite possibilities and totally uncompromising broncolor quality. Specially developed by broncolor, the world's first app for light control - "bronControl".**

**It is remarkable for its ultra-fast flash durations, an enormous control range and short charging times. Siros is powerful and universal. Enclosed in a robust housing, and providing 800 J, it can be activated using the broncolor RFS 2.1 radio release. Siros is available in standard and "S" variants, with 400 or 800 J.**

In Siros S too, the ECTC technology you know from our high-end Scoro and Move power packs controls the flash curve and guarantees flash durations from 1/13,000s (t 0.5) and constant colour over the entire control range.

The enormous control range, up to nine f-stops and down to 2 Joules gives the photographer an unrestricted choice of aperture. And the lightning-quick charging times, 0.02 to 0.9 s at 400 Joules, mean you never have to wait. broncolor has one of the most comprehensive ranges of light modifiers, and Siros is fully

integrated into this system of unlimited creative opportunities. Two new reflectors have been specially developed for Siros: an umbrella, and a size-optimised reflector, the L40, which features a snap-in system for mounting honeycomb grids.

All the basic functions of Siros can be operated using the "bronControl" app. As soon as Siros is logged in to a WiFi network, several devices in a studio, clearly identified by different-coloured LEDs, can be controlled using a smartphone or tablet.




broncolor  
siros

olor  
siros

RECONNECT  
**STUDIO 7**

INFO SETTINGS  
AUDIO 1/40 1/80 SPEED 100

< **6.0** >



- MOD. LIGHT
- TEST
- STANDBY
- MORE

**LAMPS**

- 5.0 MORE
- 5.0 MORE
- 5.0 MORE



## Siros

- Enormous control range for flash energy, up to 7 f-stops
- Flash can be triggered using RFS 2.1, PocketWizard or infrared
- Radio control using "bronControl" App or RFS 2.1
- Easy-to-use rotary controller and simple operation
- Additional function: flash sequence (flash series)
- USB connection for software updates



**Siros 400** | 31.610.XX  
**WiFi / RFS 2.1** | 31.613.XX

**Siros 800** | 31.630.XX  
**WiFi / RFS 2.1** | 31.631.XX

<b>Flash duration</b>	400 J	800 J
<b>f-stop at 2 m distance, 100 ISO</b>		
with reflector L40	22 <sup>5</sup> / <sub>10</sub>	32 <sup>8</sup> / <sub>10</sub>
with reflector P70	32 <sup>5</sup> / <sub>10</sub>	45 <sup>6</sup> / <sub>10</sub>
<b>Flash duration t 0.1 (t 0.5)</b>		
min. energy	1/350 s (1/1000 s)	1/150 s (1/500 s)
max. energy	1/700 s (1/2100 s)	1/350 s (1/1000 s)
<b>Charging time</b> (for 100% of selected energy)		
230 V/50 Hz	0.1–0.95 s	0.2–1.9 s
120 V/60 Hz	0.1–0.95 s	0.14–1.9 s
100 V/50 Hz	0.1–1.45 s	0.18–3.1 s
<b>Control range of flash energy</b>	7 f-stops in <sup>1</sup> / <sub>10</sub> or full f-stop intervals	
	6.5–400 J	13–800 J
<b>Colour temperature</b>		
max. energy/P70	5500 K	5500 K
<b>Power requirements</b>	Automatic adaptation to the mains (AC-line) voltage 100–120 V/50–60 Hz: 5.5 A, 200–240 V/50–60 Hz: 3.5 A Operation via external battery	
<b>Modelling light</b>	Halogen max. 300 W/120 V, off, proportional to flash energy or full power	
<b>Flash triggering</b>	Manual release button, photocell, sync cable, with integrated broncolor RFS 2.1	
<b>Remote Control</b>	via bronControl app for mobile devices (only for units with integrated W-Lan) RFS 2.1 transmitter (only for units with integrated RFS 2.1 receiver)	
<b>Ready display</b>	Visual and audible (can be switched off)	
<b>Additional functions</b>	- Sequences up to 50 flashes - Integrated umbrella mount and integrated umbrella reflector - USB connection for software updates	
<b>Cooling</b>	Fan, temperature controlled	
<b>Dimensions (l × w × h)</b>	32 × 13 × 18 cm (12.6 × 5.1 × 7.1")	
<b>Weight</b>	3.2 kg (7.1 lbs)	3.6 kg (7.9 lbs)
<b>Siros special accessories</b>	See page 29	



## Siros S

- Enormous control range for flash energy, up to 9 f-stops
- Flash can be triggered using RFS 2.1, PocketWizard or infrared
- Radio control using "bronControl" App or RFS 2.1
- Easy-to-use rotary controller and simple operation
- Additional function: flash sequence (flash series)
- USB connection for software updates
- Speed Mode for fast flash times (in S-Version)



### Siros 400 S WiFi / RFS 2.1 | 31.623.XX

### Siros 800 S WiFi / RFS 2.1 | 31.643.XX

<b>Flash duration</b>	400 J	800 J
<b>f-stop at 2 m distance, 100 ISO</b>		
with reflector L40	22 <sup>5</sup> / <sub>10</sub>	32 <sup>8</sup> / <sub>10</sub>
with reflector P70	32 <sup>5</sup> / <sub>10</sub>	45 <sup>6</sup> / <sub>10</sub>
<b>Flash duration t0.1 (t0.5)</b>		
min. energy	1/5500 s (1/11'000 s)	1/4000 s (1/8000 s)
max. energy	1/700 s (1/2100 s)	1/350 s (1/1000 s)
<b>Charging time</b> (for 100% of selected energy)		
230 V/50 Hz	0.02–0.95 s	0.07–1.9 s
120 V/60 Hz	0.02–0.95 s	0.04–1.9 s
100 V/50 Hz	0.02–1.4 s	0.08–2.9 s
<b>Control range of flash energy</b>	9 f-stops in 1/10 or full f-stop intervals 2–400 J	4–800 J
<b>Colour temperature</b>	ECTC technology [Enhanced Colour Temperature Control] for constant colour temperature - in speed mode ECTC is disabled.	
<b>Power requirements</b>	Automatic adaptation to the mains (AC-line) voltage 100–120 V/50–60 Hz: 5.5 A, 200–240 V/50–60 Hz: 3.5 A Operation via external battery converter possible for mains-independent operation	
<b>Modelling light</b>	Halogen max. 300 W/120 V, off, proportional to flash energy or full power	
<b>Flash triggering</b>	Manual release button, photocell, sync cable, with integrated broncolor RFS 2.1	
<b>Remote control</b>	via bronControl app for mobile devices (only for units with integrated W-Lan) RFS 2.1 transmitter (only for units with integrated RFS 2.1 receiver)	
<b>Ready display</b>	Visual and audible (can be switched off)	
<b>Additional functions</b>	- Sequences up to 50 flashes - Integrated umbrella mount and integrated umbrella reflector - Speed Mode for fastest flash durations	
<b>Speed mode (Cut-off times)</b>	<b>Siros 400 S</b>	<b>Siros 800 S</b>
	<b>Level</b>	<b>t 0.1 (t 0.5) - speed Mode</b>
	2 (1 J)	1/8500 s (1/19000 s)
	3 (3 J)	1/8500 s (1/17000 s)
	4 (6 J)	1/8000 s (1/17000 s)
	5 (12 J)	1/8000 s (1/17000 s)
	6 (25 J)	1/7500 s (1/15000 s)
	7 (50 J)	1/6500 s (1/10000 s)
	8 (100 J)	1/4000 s (1/6000 s)
	9 (200 J)	1/2500 s (1/3000 s)
	10 (400 J)	1/600 s (1/2000 s)
	<b>Level</b>	<b>t 0.1 (t 0.5) - speed Mode</b>
	2 (3 J)	1/8500 s (1/19000 s)
	3 (6 J)	1/8000 s (1/18000 s)
	4 (13 J)	1/8000 s (1/17000 s)
	5 (25 J)	1/8000 s (1/15000 s)
	6 (50 J)	1/7500 s (1/13000 s)
	7 (100 J)	1/4000 s (1/7000 s)
	8 (200 J)	1/3000 s (1/4000 s)
	9 (400 J)	1/1500 s (1/1700 s)
	10 (800 J)	1/300 s (1/1000 s)
<b>Cooling</b>	Fan, temperature controlled	
<b>Dimensions (l x w x h)</b>	32 x 13 x 18 cm (12.6 x 5.1 x 7.1")	
<b>Weight</b>	3.2 kg (7.1 lbs)	3.6 kg (7.9 lbs)
<b>Siros special accessories</b>	See page 29	

**With their outstanding light quality, Siros monolights are the perfect complement for existing studio flash installations.**

Each kit is supplied with a compact, practical Flash Bag trolley case. Accessories - such as stands, softboxes and umbrellas - can be stored in the special accessory bag, which is designed to be strapped on to the Flash Bag.

### Siros Basic Kits –

The perfect starter level kit for professionals

- 31.660.XX Siros 400 Basic Kit 2
- 31.680.XX Siros 800 Basic Kit 2
- 2 × Siros 400 or 800, 2 × umbrella silver 85 cm, 1 × synchronous cable 5 m, 2 × Basic M stand, 1 × Flash Bag 2, 1 × Accessory Bag



### Siros Expert Kits –

A step up for the pro who wants more

- 31.663.XX Siros 400 S Expert Kit 2 RFS 2.1
- 31.683.XX Siros 800 S Expert Kit 2 RFS 2.1
- 2 × Siros 400 or 800 S RFS 2.1, 1 × umbrella silver 85 cm, 1 × Softbox 60 × 60 cm incl. speed ring, 1 × synchronous cable 5 m, 2 × Basic M stand, 1 × RFS 2.1 transmitter, 1 × Flash Bag 2, 1 × Accessory Bag



### Siros Pro Kits –

Everything the demanding professional needs to get going in studio or on location

- 31.693.XX Siros 800 S Pro Kit 3 RFS 2.1
- 3 × Siros 800 S RFS 2.1, 1 × Softbox 60 × 60 cm incl. speed ring, 1 × Octabox 75 cm incl. speed ring, 2 × reflector L40, 1 × synchronous cable 5 m, 3 × Basic M stand, 1 × RFS 2.1 transmitter, 1 × Flash Bag 3, 1 × Accessory Bag




## Accessories

**Standard reflector L40**


33.115.00

Ø18.2 × 11.8 cm (7.1 × 4.6 ")


**Honeycomb grids for L40,**

33.194.00

Set of 3 pieces (narrow, middle, wide)

**Flash tube 400 / 800 J for Siros**

34.360.00

**Protecting glass**

34.369.00

5900 K

**Halogen modeling lamp 300 W / 120 V**

34.260.00

**bronControl App**

to control the Siros  
with Iphone, Ipad or Android  
App is available on Google Play Store  
and App Store

**Flash Bag 1**

36.531.00

Weight: 1.35 kg (2.9 lbs)

Dimensions: 45 × 20 × 23 cm  
(17.7 × 7.8 × 9 ")**Flash Bag 2**

36.532.00

Weight: 3.5 kg (7.7 lbs)

Dimensions: 106 × 20 × 24 cm  
(41.7 × 7.8 × 9.4 ")**Flash Bag 3**

36.533.00

Weight: 4.5 kg (9.9 lbs)

Dimensions: 103 × 21 × 37 cm  
(40.5 × 8.2 × 14.5 ")**Accessory Bag**

36.535.00

Weight: 1.25 kg (2.75 lbs)

Dimensions: 102 × 14 × 20 cm  
(40.1 × 5.5 × 7.8 ")**Basic M stand**

35.105.00

Air-cushioned (AC) with  
three sectionsAdjustable from 91 to 244 cm  
(35.8 to 96 ")


Stud 16 mm (0.6 "), Weight 1.5 kg (3.3 lbs)

**Umbrella silver 85 cm (33.4 ")**

33.574.00

**Umbrella silver 105 cm (41.3 ")**

33.570.00





The extensive range of lamps meets every photographer's needs for creative light management. The lamp is the critical element in terms of light quality, but that quality is also influenced by other factors: the shape and coating of the flash tube, the characteristics and surface of the reflectors, the uniformity of illumination along a defined reflector axis, the match between the emission characteristics of the flash and the modelling light, the optimum colour temperature and much more besides. broncolor Pulso G, Unilite and Pulso Twin lamps all have compact dimensions, a bright halogen modelling light, fan cooling, a thermal circuit breaker and plug-in flash tubes.

With their integrated broncolor bayonet and release catch the light shapers can be rotated through 360° and changed quickly and safely. Twin lamps allow the energy of two power packs to be concentrated into one lamp. The Picolite small lamps have their own accessories and, with a Pulso adapter, can also be fitted with lightweight broncolor reflectors and other accessories. Litos, the designer lamp, was especially developed for the Senso power pack, and combines multifunctionality and compactness in one. The Litos scope of supply includes an umbrella or standard reflector. As one of the first suppliers worldwide, broncolor focuses on LED technology and in 2011 introduced

the first flash lamp with LED modelling light – the MobiLED. With 30 W (comparable with 100 W halogen) and 5500 K colour temperature, the MobiLED gives photographers the ability to merge the field of photography with film for the first time. For customised lighting, users can select from a wide range of light shapers with accessories. A variety of accessories and stands are available for all broncolor lamps to ensure ease of handling.

broncolor lights are supplied with a 5900 K flash tube, halogen modelling lamp, UV-coated 5500 K protective glass (guarantees neutral colour reproduction) and a transparent transport cap.

 Jessica Keller, Switzerland



### Pulso G lamp

- Identical light characteristics of flash tubes and modelling light
- Can be equipped with 1600 J or 3200 J flash tubes
- Plug-in flash tube and protecting glass (with mechanical safety device)
- Integrated knob-operated focusing mechanism with witness marks
- Quick release bracket
- Automatic locking mechanism of the light shaper (rotatable 360°)
- Integrated tilt with high-strength braking mechanism
- Integrated umbrella holder
- Cooling fan and thermal protection
- Automatic adaptation to the respective mains power supply (after exchange of the halogen modelling lamp)



**Pulso G lamp** | 1600 J: 32.115.XX | 3200 J: 32.116.XX

Flash energy	max. 3200 J
Modelling light (230 V)	halogen max. 650 W
Length lamp cable	5 m (16 ft)
Dimensions (Ø × l × h)	Ø 13 × 31 × 20 cm (5,1 × 12,2 × 7,8")
Weight (with cable)	3,15 kg (6,9 lbs)
Stand support	for bolts 12 mm, 3/8" thread and bolts 16 mm, 5/8"

### Unilite lamp

- Corresponding emission characteristics of flash tubes and modelling light
- Can be equipped with 1600 J or 3200 J flash tubes
- Plug-in flash tube and protecting glass (with mechanical safety device)
- Quick release bracket
- Automatic locking mechanism of the light shaper (rotatable 360°)
- Integrated tilt with high-strength braking mechanism
- Integrated umbrella holder
- Cooling fan and thermal protection
- Automatic adaptation to the respective mains power supply (after exchange of the halogen modelling lamp)



**Unilite lamp** | 1600 J: 32.113.XX | 3200 J: 32.114.XX

Flash energy	max. 3200 J
Modelling light (230 V)	halogen max. 650 W
Length lamp cable	5 m (16 ft)
Dimensions (Ø × l × h)	Ø 12,6 × 30 × 17,5 cm (4,9 × 11,8 × 6,9")
Weight (with cable)	2,8 kg (6,2 lbs)
Stand support	for bolts 12 mm, 3/8" thread and bolts 16 mm, 5/8"

### Accessories

#### Flash tube 1600 J

34.322.00 (for Unilite and Pulso G)



#### Flash tube 3200 J

34.324.00 (for Unilite and Pulso G)



#### Halogen modelling lamp 300 W / 120 V

34.225.XX Pulso G / 34.234.XX Unilite  
with fuse



#### Halogen modelling lamp 650 W / 230 V

34.226.XX Pulso G / 34.235.XX Unilite  
with fuse



#### Protecting glass

34.336.00



#### Protecting glass, mat

34.337.00



**Litos lamp (for Senso)**

- Corresponding emission characteristics of flash tube and modelling light
- Single pan-tilt locking handle
- Quick release bracket and integrated umbrella holder
- Including standard and/or umbrella reflector
- Thermal protection (fan only switches on when required)
- Plug-in flash tube and protecting glass (with triple mechanical safety device)



**Litos lamp** | 32.030.XX

Flash energy	max. 2400 J
Modelling light	300 W halogen (3.15 AF)
Cooling	temperature controlled (fan)
Length of cable	4,5 m (14,8 ft)
Dimensions (Ø×l×h)	Ø 12 × 24,3 × 17,2 cm (4,7 × 9,6 × 6,8")
Weight with cable	2,3 kg (5,1 lbs)
Stand support	for bolts 12 mm, 3/8" thread and bolts 16 mm, 5/8"

**Accessories**

**Flash tube 2400 J**

34.313.00



**Protecting glass**

34.339.00

mat: 34.340.00



**Halogen modelling lamp 300 W / 230 V**

34.233.XX

with fuse



**Lamp extension cable**

5 m: 34.153.00

10 m: 34.154.00



**MobiLED lamp**

- Built-in pan/tilt head for one-hand operation
- Quick release bracket and integrated umbrella holder
- Including standard and/or umbrella reflector
- Thermal protection (fan only switches on when required)
- Plug-in flash tube and protecting glass (with triple mechanical safety device)
- LED modelling light with a colour temperature of 5500 K, only working with Move 1200 L and Mobil



**MobiLED lamp** | 32.013.00

Flash energy	1200 J (max. 1600 J)
Modelling light	30 W LED
Length of cable	3,5 m (11,5 ft)
Dimensions (Ø×l×h)	Ø 12 × 24,3 × 17,2 cm (4,7 × 9,6 × 6,8")
Weight (without reflector and accessories)	1,7 kg (3,7 lbs)
Stand support	for bolts 12 mm, 3/8" thread and bolts 16 mm, 5/8"

**Accessories**

**Flash tube 1600 J**

34.308.00



**MobiLED Continuous light adapter**

36.129.00



**Protecting glass**

34.339.00

mat: 34.340.00



### Pulso-Twin lamp

- Corresponding emission characteristics of flash and modelling light
- Two plug-in flash tubes with single integrated protecting glass
- Quick release bracket
- Automatic locking mechanism of the light shaper (rotatable 360°)
- Built-in tilt head with locking lever for an optimal breaking effect
- Cooling fan and thermal protection



### Pulso-Twin lamp | 32.117.XX

Flash energy	max. 2 × 3200 J
Modelling light (230 V)	halogen max. 650 W, 300 W 120 V
Length lamp cable	2 × 5 m (2 × 16 ft)
Dimensions (Ø×l×h)	Ø 12 × 27,5 × 20 cm (4,7 × 10,4 × 7,8")
Weight	4 kg (8,8 lbs)
Stand support	for bolts 12 mm, <sup>3</sup> / <sub>8</sub> " thread and bolts 16 mm, <sup>5</sup> / <sub>8</sub> "

### Accessories


#### Flash tube 2 × 3200 J incl. protecting glass

34.327.00  
for Pulso-Twin



#### Halogen modelling lamp 250 W / 120 V

34.221.XX  
with fuse



#### Halogen modelling lamp 650 W / 230 V

34.226.XX  
with fuse



### Picolite small lamp

Complete system of specialized light shapers as well as crossover adapter for other broncolor light shapers

- Corresponding emission characteristics of flash tubes and modelling light
- Plug-in flash tube and protecting glass (with mechanical safety device)
- Integrated reflector
- Adapter for own accessories with small dimensions (rotatable 360°)
- Adapter for broncolor light shaper available
- Built-in tilt head with locking lever for an optimal breaking effect
- Integrated umbrella holder
- Cooling fan and thermal protection
- Automatic voltage sensing (halogen modelling lamp must be manually changed)



### Picolite small lamp | 32.021.00

Flash energy	max. 1600 J
Modelling light (230 V)	halogen max. 150 W
Length lamp cable	3,5 m (11 ft)
Dimensions (Ø×l×h)	Ø 8 × 20,5 × 13,5 cm (3,1 × 8 × 5,3")
Weight (with cable)	1,25 kg (2,7 lbs)
Stand support	for bolts 12 mm, <sup>3</sup> / <sub>8</sub> " thread and bolts 16 mm, <sup>5</sup> / <sub>8</sub> "

### Accessories

#### Flash tube 1600 J

34.308.00



#### Halogen modelling lamp 150 W / 120 V

34.202.00  
with fuse



#### Halogen modelling lamp 150 W / 230 V 34.201.00

with fuse



#### Protecting glass for Picolite

34.332.00

#### Protecting glass mat for Picolite

34.335.00



**Barn door with 4 wings**

33.244.00



**Pulso adapter**

33.501.00

allows to use lightweight reflectors and accessories of the Pulso range



**Attachment with 3 honeycomb grids and 2 aperture masks**

33.204.00



**Fresnel spot attachment**

33.631.00


light angle adjustment range 15 – 35°  
incl. mat protecting glass (34.335.00)



**Projection attachment**

33.641.00

100 mm, with mat protecting glass,  
3 aperture masks, 4 integrated templates



**Lamp extension cable for MobiLED**

34.150.00

3,5 m (11 ft)



**Picobox**

33.128.00

max. 1600 J

lamp surface 15 × 25 cm (6 × 9,8")  
with integrated spring lock



**Adapter for Mini-Satellite and Unilite**

35.213.00



**Twin articulated arm in 3 parts**

35.102.00

Twin articulated arm complete, bolt with 5/8" thread and screw device for bolt adapter, may only be used with stand clamp 32.912.00



## New light dimensions

**It is not just the form and size of Paras that impresses, but above all their unique light quality and phenomenal light output. Decisive for the creative photographer is that a Para is not just a conventional light shaper, but rather an independent lighting system: various sizes of reflector are available; the position of the lamp is always central, on the axis of the reflector; the angle influences the character of the light; the range includes three diffusers with different densities. In addition Paras can be combined with other accessories. Light-thrilled photographers are always finding new combinations and characteristics with the Para system – it offers a never-ending source of inspiration and creativity.**


### The Big Ones

The Paras are parabolic reflectors; they have 24 segments, covered with a high-gloss, tear-resistant textile reflector material. The reflector openings have diameters of 88, 133, 177, 222 and 330 cm. All reflectors are constructed of aluminum, carbon fiber or fiberglass materials resulting in the matching of lighter total weight and utmost durability. The size also determines the resulting light. The Para 330 FB immerses the whole studio in wonderful light. Even over long distances it remains soft, but without ever seeming “flat”. The light is identical and homogenous over large spaces allowing the model to move freely and spontaneously. The photographer can even stand directly in front of the light source and vary the distance to the model without influencing the light or throwing a shadow. The Para 222 is easily big enough to create typical Para light, even over medium distances of 5 – 8 m. Like its big brother it can be completely defocused, and it demonstrates substantially the same light characteristics. However, over larger distances it becomes spot-like (harder) earlier, but over short distances provides the entire variation spectrum at an earlier stage.

Light from the Para 177 is gradually approaching that from a giant spot. It is slightly more aggressive (needs a supporting fill-in light more often), but on the other hand is also more interesting on structures and has greater brilliance in the highlights. This version cannot be fully defocused to the same extent, i.e. the centre of the reflector is never completely black. The residual light does reduce the three-dimensional effect somewhat, but at the same time works to counter too hard a light mood. In addition the 177 has the big advantage that it can be realistically used in smaller studios and over shorter distances.

Besides the spectacular light shapers 177, 222 and 330 FB, the Para family includes the 88 and 133 versions. At 6 kg and 8 kg respectively, they are both lightweights. The super-compact design and patented folding mechanism ensures real convenience and enables setting up in seconds. Para 88s and 133s are even more mobile - perfect for outdoor shootings and smaller studios.

With the broncolor Para family, every shooting is a success. Unbelievable light variability, light, compact, fully compatible with flash and continuous lighting – unlimited possibilities at the highest level.






**Para 88 reflector** | 33.482.00

<b>Allowed max. energy</b>	3200 J resp. 650 W HMI
<b>F-stop at 2 m / 6 1/2 ft (10 m / 33 ft) distance</b>	64 <sup>9</sup> / <sub>10</sub> (22 <sup>8</sup> / <sub>10</sub> )
<b>Inside coating</b>	silver
<b>Dimensions (without stand)</b>	open Ø 85 × 64 cm (34 × 24") closed Ø 20 cm × 83 cm (8 × 33")
<b>Weight</b>	2,8 kg (6,2 lbs) without case
<b>Scope of delivery</b>	incl. Flash bag 2

**Para 88 Kit without adapter** | 33.483.03

<b>Allowed max. energy</b>	3200 J resp. 650 W HM
<b>F-stop at 2 m / 6 1/2 ft (10 m / 33 ft) distance</b>	focused: 90 (22) , defocused: 64 (11)
<b>Inside coating</b>	silver
<b>Dimensions (without stand)</b>	open with focusing system: Ø 85 cm × 107 cm (33 × 42") closed with focusing system: Ø 32 × 107 cm (13 × 42")
<b>Weight</b>	5,5 kg (12,1 lbs) without case
<b>Scope of delivery</b>	Para 88 reflector; Focusing device Para 88/133 with tilt head, suspension rope, flash bag 2 (without Inlay), Accessory bag

**Para 133 reflector** | 33.550.00

<b>Allowed max. energy</b>	3200 J resp. 800 W HMI
<b>F-stop at 2 m / 6 1/2 ft (10 m / 33 ft) distance</b>	focused: 64 <sup>9</sup> / <sub>10</sub> (22 <sup>8</sup> / <sub>10</sub> )
<b>Inside coating</b>	silver
<b>Dimensions (without stand)</b>	open (without stand) Ø 120 × 77 cm (47 × 30") closed Ø 102 × 20 cm (40 × 8")
<b>Weight</b>	6,7 kg (14,7 lbs)
<b>Scope of delivery</b>	incl. Flash bag 2

**Para 133 Kit without adapter** | 33.551.03

<b>Allowed max. energy</b>	3200 J resp. 800 W HMI
<b>F-stop at 2 m / 6 1/2 ft (10 m / 33 ft) distance</b>	focused: 90 <sup>4</sup> / <sub>10</sub> (22 <sup>6</sup> / <sub>10</sub> )
<b>Inside coating</b>	silver
<b>Dimensions (without stand)</b>	open (without stand) Ø 120 × 77 cm (47 × 30") closed Ø 102 × 20 cm (40 × 8")
<b>Weight</b>	10,5 kg (23,1 lbs)
<b>Scope of delivery</b>	F133; Focusing device Para 88/133 with tilt head, suspension rope, flash bag 2 (without Inlay), Accessory bag

**Para 177 kit** | 33.551.03

<b>Allowed max. energy</b>	3200 J resp. 1600 W HMI
<b>F-stop at 2 m / 6 1/2 ft (10 m / 33 ft) distance</b>	focused: 128 <sup>3</sup> / <sub>10</sub> (45 <sup>5</sup> / <sub>10</sub> )
<b>Inside coating</b>	silver
<b>Dimensions (without stand)</b>	open Ø 170 cm × 95 cm (66,9 × 37,4") closed Ø 40 cm × 95 cm (15,7 × 37,4")
<b>Weight</b>	9,5 kg (20,9 lbs)
<b>Scope of delivery</b>	Para 177, (Trolley bag foldable)

**Para 222 kit** | 33.552.03

<b>Allowed max. energy</b>	3200 J resp. 1600 W HMI
<b>F-stop at 2 m / 6 1/2 ft (10 m / 33 ft) distance</b>	focused: 128 <sup>3</sup> / <sub>10</sub> (45 <sup>5</sup> / <sub>10</sub> )
<b>Inside coating</b>	silver
<b>Dimensions (without stand)</b>	open Ø 170 cm × 95 cm (66,9 × 37,4") closed Ø 40 cm × 95 cm (15,7 × 37,4")
<b>Weight</b>	11,5 kg (25,4 lbs)
<b>Scope of delivery</b>	Para 222, (Trolley bag foldable)

**Para 330 FB** | 33.486.00

<b>Allowed max. energy</b>	3200 J
<b>F-stop at 2 m / 6 1/2 ft (10 m / 33 ft) distance</b>	focused: 90 8/10 (32 9/10)
<b>Inside coating</b>	silver
<b>Dimensions (without stand)</b>	open: Ø 330 × 240 cm (130 × 95") closed: 32 × 160 cm (12,6 × 63")
<b>Weight</b>	12,1 kg (26,6 lbs)
<b>Scope of delivery</b>	incl. suspension ropes (without bag)

Stands and lamps are not included



**Accessories**

**Focusing Rod F**

- Para 88: 33.703.00
- Para 133: 33.705.00
- Para 177: 33.707.00
- Para 222: 33.708.00



**Adapter P**

- 33.489.01 for standard broncolor mount



**Focusing device Para with tilt head, suspension rope**

- 33.700.00 (can be ordered separately 33.504.00 for focusing device and 33.506.00 for tilt head)



**Adapter D**

- 33.489.01 for broncolor HMI Daylight 200/400



**Tilt head with crank handle for Para / Para FB**

- 33.477.00 Recommended when using light devices over 5 kg (11 lbs).



**Adapter Profoto**

- 33.489.03




**Light grid 40°**

- Para 88: 33.221.00
- Para 133: 33.232.00
- Para 177: 33.230.00



**Adapter K5600**

- 33.489.05 for focusing system for Para 88 / 133
- 33.489.08 for focusing system for Para 177 / 222



**Diffuser no. 1 (low\*)**

- Para 88: 33.472.00 / Para 133: 33.293.00
- Para 177: 33.287.00 / Para 222: 33.290.00
- Para 330 FB: 33.469.00

**Diffuser no. 2 (medium\*)**

- Para 88: 33.473.00 / Para 133: 33.294.00
- Para 177: 33.288.00 / Para 222: 33.291.00
- Para 330 FB: 33.470.00

**Diffuser no. 3 (high\*)**

- Para 88: 33.474.00 / Para 133: 33.295.00
- Para 177: 33.289.00 / Para 222: 33.292.00




**Adapter Ringflash**

- 33.489.04



**Universal adapter to non-broncolor lamps**

- 33.489.06



\*Diffusion degree

The slightly textured open reflectors are characterised by homogeneous light distribution, although a controlled centre emphasis can be achieved using focusable Pulso G lamps.

The light angle of each open reflector is apparent from its model designation, optical attachments (such as projection attachment) offer a variable coverage angle.

**Standard reflector P70**

33.107.00  
 optimised for Pulso G  
 and Unilite lamps  
 Ø 23,2 × 18,4 cm [9,1 × 7,2"]




**Honeycomb grids for P70**

33.207.00  
 set of 3 pieces (fine, medium, coarse)



**Honeycomb grid extremely narrow for P70**

33.202.00




**Barn door for P70**

33.227.00  
 with 2 wings, with 2 clips to fix diffusers,  
 filters and masks




**Barn door for P70**

33.247.00  
 with 4 wings, with 2 clips to fix diffusers,  
 filters and masks




**Colour filters for P70**

33.307.00  
 set of 12 pieces



**Grey and correcting filters for P70**

33.317.00  
 set of 12 pieces



**Opal diffusers for P70**

33.327.00  
 set of 12 pieces



**Standard reflector P65**

33.106.00  
 optimised for Pulso-Twin  
 and Pulso 8 lamps  
 Ø 29,5 × 24 cm [11,6 × 9,4"]



**Honeycomb grid extremely narrow for P65 and P45**

33.211.00




**Honeycomb grids for P65, P45 and PAR**

33.206.00  
 set of 3 pieces (fine, medium, coarse)




**Narrow angle reflector P45**

33.104.00  
 optimised for Pulso G  
 and Unilite lamps  
 Ø 29,5 × 35,3 cm [11,6 × 13,9"]



**Barn door with 4 wings for P65, P45 and PAR**

33.246.00  
 with 2 clips to fix diffusers,  
 filters and masks



**PAR Reflector**

33.113.00  
 light angle 48°, with protecting glass UV, mat  
 Ø 29,5 × 18,3 cm [11,6 × 7,2"]



**Colour filters for P65, P45, PAR and background reflector**


33.306.00  
 set of 12 pieces



**Standard reflector L40**


33.115.00

optimized for Siros  
400 und Siros 800  
Ø 182 × 118 cm (71,6 × 46,4 ")

**Honeycomb grids for L40**


33.194.00

set of 3 pieces (fine, medium, coarse)

**Background reflector**

33.114.00

Ø 12,7 / 19 × 30,3 cm (5 / 7,5 × 11,8")

**Narrow angle reflector P50**


33.105.00

optimised for Pulso-Twin  
and Pulso 8 lamps  
Ø 34,5 × 39,4 cm (13,6 × 15,5")

**Honeycomb grids for P50**

33.205.00

set of 3 pieces (fine, medium, coarse)


**Softlight reflector P-Soft**

33.110.00

silver inside coating  
Ø 51.8 × 19,6 cm (20,4 × 7,7")

**Diffuser filter for Softlight reflector P-Soft and Beauty Dish**

33.310.00


**Beauty Dish reflector**

33.111.00

with textile diffusor,  
white inside coating,  
incl. bag (36.516.00)  
Ø 51.8 × 19,6 cm (20,4 × 7,7")

**Honeycomb grid for Softlight reflector P-Soft and Beauty Dish**

33.210.00

**P-Travel reflector**


33.103.00

light angle 55°  
Ø 19,5 × 9 cm (7,7 × 3,5")

**Barn door for P-Travel**

33.243.00

with 2 wings

**Wide angle reflector P120**

33.112.00

Ø 22 × 4,4 cm (8,6 × 1,7")

**Conical snoot**


33.120.00

Ø 13,8 / 7,6 × 26,25 cm (5,4 / 2,9 × 10,3")

**Spot attachment**

33.640.00

with mat protecting glass,  
6 aperture masks, 1 gobo holder

**UV attachment**

33.626.00 Ø 18,3 × 14,5 cm (Ø 7,2 × 5,7") 0,74 kg (1,6 lb)

light angle approx. 70°



The broncolor Softboxes are optimised light shapers in 9 different shapes and sizes. Rectangular, square, octagonal and as a strip. These quality, high-performance light shapers extend your flash system and offer countless additional lighting effects. The two diffusers included in the scope of supply enable a soft light with very uniform distribution. With optional light grids and additional diffusers, light control

can be made even more precise. The highly-effective internal coating ensures a high efficiency. Coloured markings on the tensioning rods and on the Speedring enable simple, quick erection and dismantling. With appropriate Speedrings, Softboxes can also be used with flash units from other manufacturers.

**Softbox**

33.560.00	35	x	60	cm	1,1	x	2	ft
33.561.00	60	x	60	cm	2	x	2	ft
33.562.00	60	x	100	cm	2	x	3,3	ft
33.563.00	100	x	100	cm	3,3	x	3,3	ft
33.564.00	30	x	120	cm	1	x	3,9	ft
33.565.00	90	x	120	cm	3	x	3,9	ft
33.567.00	30	x	180	cm	1	x	5,9	ft
33.566.00	120	x	180	cm	3,9	x	5,9	ft

**Additional front diffuser for Softbox**

33.590.00	35	x	60	cm	1,1	x	2	ft
33.591.00	60	x	60	cm	2	x	2	ft
33.592.00	60	x	100	cm	2	x	3,3	ft
33.593.00	100	x	100	cm	3,3	x	3,3	ft
33.594.00	30	x	120	cm	1	x	3,9	ft
33.595.00	90	x	120	cm	3	x	3,9	ft
33.599.00	30	x	180	cm	1	x	5,9	ft
33.596.00	120	x	180	cm	3,9	x	5,9	ft

**Strip mask for Softbox**

33.610.00	30	x	120	cm	1	x	3,9	ft
33.611.00	30	x	180	cm	1	x	5,9	ft

**Octabox**

33.600.00	Ø 75 cm	2,5	ft
33.601.00	Ø 150 cm	4,9	ft

**Additional diffuser for Octabox**

33.597.00	Ø 75 cm	2,5	ft
33.598.00	Ø 150 cm	4,9	ft

**Light grid 40° for Octabox**

33.587.00	Ø 75 cm	2,5	ft
33.588.00	Ø 150 cm	4,9	ft



**Light grid 40° for Softbox**

33.580.00	35	x	60	cm	1,1	x	2	ft
33.581.00	60	x	60	cm	2	x	2	ft
33.582.00	60	x	100	cm	2	x	3,3	ft
33.583.00	100	x	100	cm	3,3	x	3,3	ft
33.584.00	30	x	120	cm	1	x	3,9	ft
33.585.00	90	x	120	cm	3	x	3,9	ft
33.567.00	30	x	180	cm	1	x	5,9	ft
33.586.00	120	x	180	cm	3,9	x	5,9	ft




**Beautybox 65**

33.568.00 including one double-sided counter reflector (gold/white), one transparent counter reflector and one diffuser

**Light grid 40° for Beautybox 65**

33.579.00 Ø 65 cm (2,1 ft)



**Adapter rings for Softboxes, Octaboxes and Beautybox 65**

33.401.00 broncolor

33.401.01 Profoto

33.401.02 Hensel

33.401.03 Elinchrom

33.401.04 Bowens

33.401.07 Canon/Nikon



**The classic in lighting composition**

broncolor Umbrellas are produced in two sizes and three different versions. Silver, white and translucent, and 85 cm or 105 cm in diameter.

**Umbrella silver**

33.574.00: Ø 85 cm (2,8 ft)

33.570.00: Ø 105 cm (3,4 ft)



**Umbrella transparent**

33.575.00: Ø 85 cm (2,8 ft)


33.572.00: Ø 105 cm (3,4 ft)



**Umbrella white**

33.573.00: Ø 85 cm (2,8 ft)

33.571.00: Ø 105 cm (3,4 ft)



**Umbrella reflector for Pulso G and Unilite lamps**

33.496.00





**Mini-Satellite**

33.152.00

f-stop at 2 m (6 ½ ft) distance,  
 100 ISO with 3200 J: 180 <sup>2</sup>/<sub>10</sub>,  
 parabolic reflector Ø 60 × 15 cm (23 × 6")  
 incl. protecting glass mat UV,  
 additional reflector,  
 light angle adjustment range  
 18° – 30° (from 3 m | 10 ft distance)

**Unilite holder for Mini-Satellite**

35.213.00

**Satellite Staro**

33.151.00

f-stop at 2 m (6 ½ ft) distance,  
 100 ISO with 3200 J: 45 <sup>2</sup>/<sub>10</sub>,  
 parabolic reflector  
 Ø 88 × 25 cm (35 × 14")  
 incl. mat Plexiglas diffuser,  
 bracket

**Honeycomb grid for Satellite Staro**

33.209.00

**broncolor Flooter**


32.431.00

max. 6400 J

f-stop at 2 m (6 ½ ft) distance,  
 100 ISO with 3200 J: (15°) 90 <sup>2</sup>/<sub>10</sub>  
 24 × 46 × 52 cm (9,4 × 18 × 20,5")  
 light angle adjustment range 15° – 70°,  
 incl. fixing bracket, Fresnel lens


**Honeycomb grid for broncolor Flooter**

33.208.00

**Barn doors for broncolor Flooter**

33.225.00

set of 2 pieces





### Ringflash C

- Halogen modelling light 200 W
- A honeycomb set (3 pieces) is available for Ringflash C
- High-strength UV-coated flash tube (3200 J)
- Powerful fan cooling and integrated UV-filter
- Operation possible on all mains power supplies worldwide



Ringflash C | 32.462.XX

Flash energy	max. 3200 J
Modelling light (230 V)	200 W halogen: 10 × 20 W / 24 V
F-stop at 2 m (6 ½ ft), 100 ISO	45 1/10 (3200 J) with soft reflector: 45 6/10 (3200 J)
Cooling	stabilised with 2 fans
Dimensions with support (Ø×h×d)	23,1 × 28,6 × 18 cm (9,1 × 11,3 × 7,1")
Weight with cable 5 m (16 ft)	2,7 kg (6 lbs)

### Ringflash P for Para 88 / 133 / 177 / 222 and 330 FB

- Halogen modelling lamp 200 W
- High-strength UV-coated flash tube (3200 J) and protecting glass
- Powerful fan cooling and integrated UV-filter
- Operation possible on all mains power supplies worldwide
- In combination with Para FB a perfect front focusing, which enables different light angles and characteristics



Ringflash P for Para 330 FB | 32.461.XX  
 Ringflash P for Para 88 / 133 / 177 / 222 | 32.463.XX

Flash energy	max. 3200 J
Modelling light (230 V)	200 W halogen: 10 × 20 W / 24 V
f-stop at 2 m (6 ½ ft) distance, 100 ISO with 3200 J	with Para 88: 90 [22] with Para 133: 90 [22] with Para 177: 128 3/10 (45 5/10) with Para 222: 32 5/10 (11 1/10) with Para 330 FB: 90 7/10 (32 8/10)
Cooling	stabilised with 2 fans
Dimensions with support (Ø×h×d)	23,1 × 19,4 × 14 cm (9,1 × 7,6 × 5,5")
Weight with cable 5 m (16 ft)	2,2 kg (4,9 lbs)
Support	for Para 88 / 133 / 177 / 222 / 330 FB

### Accessories

#### Halogen modelling lamp

20 W / 24 V: 34.216.00 (230 V)  
 20 W / 12 V: 34.217.00 (120 V)  
 for Ringflash C / Ringflash P



#### Honeycomb grid for Ringflash C

33.219.00  
 set of 3 pieces (fine, medium, coarse)



#### Power reflector for Ringflash C

33.125.00  
 slightly satiny inner surface coating



#### Honeycomb grid for Power reflector

33.189.00



#### Soft reflector for Ringflash C

33.123.00  
 silver inside coating  
 incl. UV-coated protecting glass



#### Conversion set for Ringflash C

36.125.00  
 for conversion to Ringflash P



#### Beauty reflector for Ringflash C

33.124.00  
 white inside coating  
 incl. UV-coated protecting glass



#### Conversion set for Ringflash P

36.126.00  
 for conversion to Ringflash C



**Pulso-Spot 4**

32.425.XX (5500 K\*)

max. 3200 J

37 × 29 × 25 cm (14,5 × 11,4 × 9,8")

f-stop at 2 m (6 ½ ft)

distance, 100 ISO: 90

with fixing bracket, flash tube,

modelling lamp, Fresnel lens

(UV coating), light angle

adjustment range 15° – 40°,

cable 5 m (16 ft)

Weight with cable 8,25 kg (18,2 lb)

**Flash tube 3200 J**

34.344.00

**Halogen modelling lamp 300 W / 230 V**

34.223.XX

with fuse


**Halogen modelling lamp 250 W / 120 V**

34.221.XX

with fuse

**Barn door with 2 wings for Pulso-Spot 4**

33.224.00


**Optical snoot 150 mm for Pulso-Spot 4**

33.620.55 (5500 K\*)

150 mm (5,9")

with 6 masks, gobo holder,

filter with holder

**Templates for spot attachment**

33.623.00

for Pulso-Spot 4, set of 4 pieces

**Gobo set for spot attachment**

33.625.00

for Pulso-Spot 4, set of 12 pieces

**Sunlite Set for Pulso G / Unilite**

33.162.00 (5500 K\*)

max. 3200 J, f-stop at 2 m (6 ½ ft) distance, 100 ISO: 22<sup>8/10</sup>

comprises:

1 U-shaped special flash tube, 1 clear protecting glass,

1 mat protecting glass, 1 barn door with 4 wings,

for effects similar to UV-sunlight

**Litestick**

32.451.00 (5500 K\*)

max. 3200 J, 5,5 × 57 cm (2,1 × 22,4"), f-stop at 2 m (6 ½ ft) distance,

100 ISO: 45.7 (with reflector), 32<sup>7/10</sup> (without reflector),

with flash tube, removable reflector, stand adapter, cable 3,5 m (11 ½ ft)

**Balloon**

33.161.00

max. 3200 J

for Pulso G and Unilite lamps, monolights,

acrylic glass sphere, opal, Ø 50 cm (20"),

with black plastic socket and Pulso bayonet




**Lightbar 60 Evolution**

32.351.XX (5500 K)  
 Flash energy max. 3200 J  
 f-stop at 2 m (6 ½ ft) distance, 100 ISO: 32 <sup>5</sup>/<sub>10</sub>  
 with "tunnel-shaped" Plexiglas diffuser,  
 interchangeable tilt head, fan, 2 flash tubes,  
 10 modelling lamps 20 W, cable 5 m (16 ft)  
 Dimensions (l×w×h) 58 × 12 × 13 cm (23 × 5 × 5")  
 Weight 3,6 kg (8 lbs)



**Barn doors for Lightbar /  
 Striplite 60 Evolution**

33.228.00



**Plexiglas cap mat,  
 for Lightbar 60 Evolution**

33.272.00



**Striplite attachment  
 for Lightbar 60 Evolution**

33.274.00




**Lightbar 120 Evolution**

32.353.XX (5500 K)  
 Flash energy max. 3200 J  
 f-stop at 2 m (6 ½ ft) distance, 100 ISO: 45 <sup>5</sup>/<sub>10</sub>  
 with "tunnel-shaped" Plexiglas diffuser,  
 interchangeable tilt head, fan, 4 flash tubes,  
 20 modelling lamps 20 W, 2 cables 2 × 5 m (16 ft)  
 Dimensions (l×w×h) 112 × 12 × 13 cm (44 × 5 × 5")  
 Weight 6,8 kg (15 lbs)



**Barn doors for Lightbar /  
 Striplite 120 Evolution**

33.229.00



**Plexiglas cap mat,  
 for Lightbar 120 Evolution**

33.273.00




**Striplite attachment  
 for Lightbar 120 Evolution**

33.275.00




**Striplite 60 Evolution**

32.301.XX (5500 K)  
 Flash energy max. 3200 J  
 f-stop at 2 m (6 ½ ft) distance, 100 ISO: 32 <sup>1</sup>/<sub>10</sub>  
 with Plexiglas diffuser, interchangeable tilt head,  
 fan, 2 flash tubes, 10 modelling lamps 20 W,  
 cable 5 m (16 ft)  
 Dimensions (l×w×h) 58 × 12 × 13 cm (23 × 5 × 5")  
 Weight 3,6 kg (8 lbs)



**Barn doors for Lightbar /  
 Striplite 60 Evolution**

33.228.00



**Lightbar attachment,  
 Plexiglas cap mat,  
 for Striplite 60 Evolution**

33.272.00



**Honeycomb grid  
 for Striplite 60 attachment**

33.217.00



**Striplite 120 Evolution**

32.303.XX (5500 K)

Flash energy max. 3200 J


f-stop at 2 m (6 ½ ft) distance, 100 ISO: 45

max. 2 × 3200 J, with Plexiglas diffuser,  
interchangeable tilt head, fan, 4 flash tubes,

20 modelling lamps 20 W, 2 cables 2 × 5 m (16 ft)

Dimensions (l×w×h) 112 × 12 × 13 cm (44 × 5 × 5")

Weight 6,8 kg (15 lbs)

**Barn doors for Lightbar / Striplite 120 Evolution**

33.229.00

**Lightbar attachment, Plexiglas cap mat, for Striplite 120 Evolution****Honeycomb grid for Striplite 120 Evolution**

33.218.00

**Accessories****Halogen modelling lamp 20 W / 24 V**

34.216.00

for Lightbar / Striplite 60 / 120 Evolution

230 V

**Halogen modelling lamp 20 W / 12 V**

34.217.0

for Lightbar / Striplite 60 / 120 Evolution

120 V

**Boxlite 40**

32.341.XX (5500 K)

Flash energy max. 3200 J

f-stop at 2 m (6 ½ ft) distance,

100 ISO: 22<sup>3/10</sup> (1600J)

with 2 flash tubes, 4 modelling lamps,

quick change head, cable 5 m (16 ft)

Dimensions (l×w×h) 30 × 40 × 15 cm (11,8 × 15,7 × 5,9")

(measurements without quick change head)

Weight 4,1 kg (9 lbs)

**Modelling lamp 40 W for Boxlite 40**

34.211.XX

**Hazylight-Soft**

33.513.00

f-stop at 2 m (6 ½ ft) distance,

100 ISO: 45 (3200J)

with white inside coating,

bracket and ring,

for Pulso G and Unilite lamps


Dimensions (l×w×h) 104 × 104 × 43 cm

(40 × 40 × 17"),

Weight 16,9 kg (37,3 lbs)

**Honeycomb grid for Hazylight-Soft**

33.215.00



**RFS 2.1**

Number of work stations	99
Number of frequency channels	40
Frequency	2,4 GHz
Transmission time (transmitter to receiver)	0,425 µs
Operating distance outdoors	up to 200 m (656 ft)
Operating distance in closed rooms	up to 50 m (164 ft)
Max. trigger sequence per second	100
Power supply	RFS 2 transmitter: 3 V CR2450 battery RFS 2 receiver: USB power supplier
Dimensions (l×w×h)	6,8 × 3,9 × 2,5 cm (2,7 × 1,5 × 1")
Weight (incl. battery)	43 g (0,09 lb)



**RFS 2.1 transmitter kit** | 36.133.00

1 transceiver, 1 lithium button cell CR 2450, 1 sync cable for camera, 1 sheath

**RFS 2.1 receiver kit** | 36.134.00

1 transceiver, 1 base plate, 1 lithium button cell CR 2450, 1 sync cable for camera, 1 sync cable for flash unit, 1 USB power supplier for receiver-operation (incl. supplier), 1 car charging cable, 1 USB cable, 1 sheath

**RFS 2.1 transmitter / receiver kit** | 36.135.00

2 transceivers, 1 base plate, 1 lithium button cell CR 2450, 1 sync cable for camera, 1 sync cable for flash unit, 1 USB power supplier for receiver-operation (incl. supplier), 1 car charging cable, 1 USB cable, 2 sheaths

**Sender RFS** | 36.130.00

Comprises	Transmitter with lithium button cell, 1 sync cable
Power regulation	in 1/1 and 1/10 f-stops
Number of frequency channels	10
Operational distances: outdoors	30 – 50 m (98 – 164 ft)
Operational distances: in closed rooms	20 – 30 m (65 – 98 ft), possible range up to 300 m (984 ft)
Dimensions(l×w×h)	7,2 × 4,7 × 5,7 cm (2,5 × 1,8 × 2,2")
Weight	55 g (0,12 lbs)



**RFS transceiver** | 36.131.00

Comprises	Transceiver with base plate, 1 USB connection cable, 1 sync cable, 1 data carrier with software
Power regulation	in 1/1 and 1/10 f-stops
Number of frequency channels	10
operational distances: outdoors	30 – 50 m (98 – 164 ft)
in closed rooms	20 – 30 m (65 – 98 ft), possible range up to 300 m (984 ft)
Dimensions (l×w×h)	8 × 5,6 × 5,2 cm (3,1 × 2,1 × 2")
Weight	105 g (0,23 lbs)
System requirements	requires a serial USB interface
Computer requirements	Apple Macintosh with OS 8.6 or higher (OS 9.1 or higher recommended), OS X, approx. 5 MB free memory space, or PC with Microsoft Windows 98 / WinMe / Win2000 / Windows XP / Vista, USB interface, approx. 5 MB free memory space



**HotShoe Adapter 2 in 1** | 36.137.00

Combines any two triggers from this list: broncolor RFS, RFS 2, RFS 2.1, PocketWizard PlusX, Plus III and MultiMax (without any delay)



**IRX 2** | 36.116.00

Infrared transmitter with 2 channels for cordless triggering, range approx. 50 m (160 ft), with 1 sync cable and 2 batteries 1.5 V



		Siros 400 (S) / 800 (S)	Litos lamp / MobileLED	Unilite lamp	Pulso G lamp	Pulso-Twin lamp	Picolite with Pulso adapter	Ringflash P lamp
<b>Reflectors</b>	Standard reflector L40	●	●				●	
	Standard reflector P70	●	●	●	● 3	●	●	
	Standard reflector P65	●	● 1	● 1	● 3	●	●	
	Narrow angle reflector P45	●	●	●	● 3	●	●	
	Narrow angle reflector P50	●	● 1	● 1	● 3	●	●	
	Softlight reflector P	●	●	●	●		●	
	Beauty Dish reflector	●	●	●	●	●	●	
	Wide angle reflector P120	●	●	●	●	●	●	
	PAR reflector	● 2	● 6	● 6	● 6			
	P-Travel reflector	●	●	●	●	●	●	
	Conical snoot	●	●	●	●	●	●	
	UV attachment	● 7	● 7	● 7	● 7	● 4		
	Umbrella reflector	●	●	●	●	●		
	Spot attachment	●	●	●	●			
	Sunlite-Set		●	●	●			
	broncolor Flooter	●	●	●	●	● 2		
	Mini-Satellite			● 5	●	●	●	
	Satellite Staro	●	●	●	●	● 4	● 1	
	Para 88 reflector / P Kit	● 7	●	●	●	●	●	●
	Para 133 reflector / P Kit	● 7	●	●	●	●	●	●
Para 177 / 222	● 7	●	●	●	●	●	●	
<b>Softboxen</b>	35 × 60	●	●	●	●	●	● 1	
	60 × 60	●	●	●	●	●	● 1	
	60 × 100	●	●	●	●	●	● 1	
	100 × 100	●	●	●	●	●	● 1	
	30 × 120	●	●	●	●	●	●	●
	90 × 120	●	●	●	●	●	●	●
	30 × 180	●	●	●	●	●	●	●
	120 × 180	●	●	●	●	●	●	●
<b>Softbox Flex</b>	70 × 70	●	●	●	●	●	●	
<b>Octaboxen</b>	Ø 75	●	●	●	●	●	● 1	
	Ø 150	●	●	●	●	●	● 1	
<b>Beautybox 65</b>	Ø 65	●	●	●	●	●	●	
<b>Special effect lamps</b>	Balloon	●	●	● 8	● 8	● 8	●	
	Hazylight-Soft			●	●			

● recommended combination  
 ● not recommended combination

1 centre-focus light  
 2 non-optimized illumination  
 3 adjustable illumination, heavily centre-focused till uniform  
 4 up to 3200 J

5 with Unilite holder 35.213.00  
 6 with mat protecting glass 34.340.00  
 7 remove protecting glass  
 8 no modeling light

**Basic M stand**

35.105.00

Air-cushioned (AC) with three sections  
Adjustable from 91 to 244 cm (35.8 to 96"),  
Stud 16 mm (0.6"),  
weight 1.5 kg (3.3 lbs)

**Super boom**

35.140.00

boom arm with counter-weight,  
length 210 cm (7 ft),  
with holder (35.146.00)  
for steel stand  
weight 9,9 kg (22 lbs)

**Junior stand AC**

35.100.00

air cushioned (AC), with 2 height  
extensions, adjustable from  
90 to 250 cm (3 – 8 ft),  
and 3/8" threaded bolt 16 mm,  
weight 1,25 kg (2,7 lbs)

**Mini-Flamingo stand**

35.170.00

stand on casters with platform  
for power pack as counter-weight,  
crank handle and cable suspension,  
arm length 107 cm (3,4 ft),  
max. height 260 cm (8,5 ft),  
incl. broncolor threaded bolt,  
lamp adapter and angle adapter,  
weight 24 kg (53 lbs)

**Senior stand AC**

35.110.00

air cushioned (AC), with 2 height  
extensions, adjustable from  
110 to 260 cm (3,6 – 8,1 ft),  
and 3/8" threaded bolt 16 mm,  
weight 2,1 kg (4,6 lbs)

**Flamingo stand**

35.210.00

stand on casters with platform  
for power pack and container  
for counter-weight, crank handle  
and cable suspension,  
arm length 150 cm (5 ft),  
max. height 325 cm (10 ft)  
weight 43 kg (95 lbs)

**Casters for Senior stand**

35.111.00

set of 3 pieces

**XXL stand AC**

35.114.00

air cushioned (AC), with 3 height  
extensions as well as  
stand casters, adjustable from  
144 – 455 cm (4,7 – 14,9 ft),  
stand mount 28 mm (1,1"),  
3/8" threaded bolt 16 mm,  
weight 8 kg (17,6 lbs)

**Hazylight stand**

35.200.00

stand on casters with platform  
for power pack, counter-weight  
and cable suspension  
arm 85 cm (2,6 ft)  
max. height 270 cm (9 ft)  
weight 38 kg (84 lbs)



**Striplite holder**

35.216.00  
for Flamingo stand



**Double bolt (A)**

35.297.00  
Ø 16 mm



**Bolt (B)**

38989.00  
Ø 16 mm 3/8" et 1/4" internal thread



**Recommended fastening of stand**

	Para FB 330	Para 177 / 222	Para 88 P kit	Para 88 reflector	Para 133 effector	Para 133 P kit	Siros 400(S) / 800(S)	Litos MobileLED	Unilite	Lamps Pulso G und Pulso Twin	broncolor Flooter	Pulso-Spot 4	Boxlite 40	Hazylight-Soft	Lightbar / Striplite 60/120 Evolution	Picolite / Litestick
<b>JJunior stand</b> with bolt 16 mm 35.100.00			●	●	●	●	●	●	●	●	●	●	●		●	●
<b>Basic M Stativ</b> with bolt 16 mm 35.105.00							●	●	●	●	●	●	●	●	●	●
<b>Senior stand</b> with bolt 16 mm 35.110.00			●	●	●	●	●	●	●	●	●	●	●		●	●
<b>XXL Stand</b> with bolt 16 mm 35.114.00 and with pod Ø 28 mm	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
<b>Super boom</b> 35.140.00				●				●	●	●			●		●	●
<b>Mini-Flamingo stand</b> 35.170.00		●	●	●	●	●	● B	B	B	B	B	●				B
<b>Flamingo stand</b> 35.210.00														●		
<b>Hazylight stand</b> 35.200.00														●		
<b>Stands of other brands</b> with pod Ø 16 mm			A	A	A	● A	A	A	A	A	A	A	A		A	
with pod Ø 28 mm	●	●	●	●	A	●					●	●				

● No further holder necessary

A-B Holder necessary

● Fastening is not recommended




broncolor lamps and monolights are supplied with flash tube 5900 K, halogen modelling lamp, UV-coated protecting glass 5500 K (guarantees neutral colour reproduction) and transparent protection cap.

You will find all the spare parts on [www.broncolor.com](http://www.broncolor.com)

**Siros 400 / 800 / 400S** (Page 27)

**Flash tube 400/800 J to Siros**

34.360.00



**Halogen modelling lamp 300 W / 120 V**

34.260.00



**Protecting glass**

34.369.00

5900 K



**Unilite, Pulso G** (Page 31)

**Flash tube 1600 J**

34.322.00



**Flash tube 3200 J**

34.324.00



**Halogen modelling lamp 300 W / 120 V**

34.225.XX Pulso G / 34.234.XX Unilite  
with fuse



**Halogen modelling lamp 650 W / 230 V**

34.226.XX Pulso G / 34.235.XX Unilite  
with fuse



**Protecting glass**

34.336.00



**Protecting glass, mat**

34.337.00



**Pulso Twin** (Page 33)

**Flash tube 2 x 3200 J**

34.327.00

with fuse



**Halogen modelling lamp 650 W / 230 V**

34.226.XX

with fuse



**Halogen modelling lamp 250 W / 120 V**

34.221.XX

with fuse



**Picolite** (Page 34)**Flash tube 1600**

34.308.00

**Halogen modelling lamp 150 W / 230 V (Picolite)**

34.201.00

with fuse

**Halogen modelling lamp 150 W / 120 V (Picolite)**

34.202.00

with fuse

**Halogen modelling lamp 100 W / 12 V**

34.203.00

with fuse

**Protecting glass**

34.332.00

**Protecting glass, mat**

34.335.00

**Litos** (Page 32)**Flash tube 2400 J**

34.313.00

**Halogen modelling lamp 300 W / 230 V**

34.233.XX

with fuse

**Protecting glass**

34.339.00

**Protecting glass, mat**

34.340.00

**Ringflash P / C** (Page 46) **Lightbar / Striplite** (Page 48 – 49)**Halogen modelling lamp 20 W / 24 V**

34.216.00

230 V

**Halogen modelling lamp 20 W / 12 V**

34.217.00

120 V

**Pulso Spot 4** (Page 47)**Flash tube 3200 J**

34.344.00

**Halogen modelling lamp 250 W / 120 V** 34.221.XX

with fuse

**Halogen modelling lamp 300 W / 230 V** 34.223.XX

with fuse

**Boxlite 40** (Page 49)**Modelling lamp 40 W**

34.211.XX

**MobiLED** (Page 32)**Flash tube 1600 J**

34.308.00

**Protecting glass**

34.339.00

**Protecting glass, mat**

34.340.00



**Beauty Dish bag**

36.516.00  
for Beauty Dish and P-Soft  
Dimensions: 54 × 22 cm (21,2 × 8,5 ")



**Flash bag 1**

36.531.00  
for Siros  
Weight: 1.35 kg (2,2 lbs)  
Dimensions:  
45 × 20 × 23 cm (17,7 × 7,8 × 9 ")



**Outdoor trolley backpack for Senso and Move**

36.519.00  
Weight: 5 kg (11 lbs)  
Dimensions: 56 × 41 × 27 cm (22 × 16,1 × 10,6 ")



**Flash bag 2**

36.532.00  
for Siros, Para 88 and Para 133  
Weight: 3.5 kg (6,6 lbs)  
Dimensions: 106 × 20 × 24 cm (41,7 × 7,8 × 9,4 ")



**Move 1200 L protective bag**

36.520.00  
Weight 0.9 kg (1,9 lbs)  
Dimensions: 24 × 19 × 30 cm (9,4 × 7,5 × 11,8 ")



**Flash bag 3**

36.533.00  
for Siros  
Weight: 4.5 kg (8,8 lbs)  
Dimensions: 103 × 2 × 37 cm  
(40,5 × 8,2 × 14,5 ")



**Move 1200L Battery Pouch**

36.552.00  
for standalone use with continuous  
light adapter and MobiLED head  
Weight: 0.2 kg (0,4 lbs)  
Dimensions: 21 × 14 × 7 cm (8,2 × 5,5 × 2,7 ")



**Accessory bag**

36.535.00  
for Siros  
Weight: 1.25 kg (1,25 lbs)  
Dimensions: 102 × 14 × 20 cm  
(40,1 × 5,5 × 7,8 ")



**Sync cable**

34.111.00: 5 m (16 ft)  
34.112.00: 10 m (32 ft)

**Custom length lamp cable (per meter)**

34.159.00 Pulso G / Unilite

**Lamp extension cable for MobiLED**

34.150.00: 3,5 m (11 ft)  
34.155.00: 10 m (32 ft)

**Lamp extension cable for lamps up to max. 3200 J**

34.151.00: 5 m (16 ft)  
34.152.00: 10 m (32 ft)


**Extension cable Litos**

34.153.00: 5 m (16 ft)  
34.154.00: 10 m (32 ft)

**Trolley bag (foldable)**

36.521.00  
for Para 177 / 222  
Dimensions: 123 × 40 × 42 cm (48,4 × 15,7 × 16,5 ")  
Weight: 2.55 kg (4,4 lbs)






## The Future of Photography before Your Very Eyes

# GEN broncolor ▶ NEXT

The concept behind broncolor's Gen NEXT is easy – broncolor equips the emerging generation of young professional photographers with innovative lighting systems for photography and videography and sets them the following task: convince us with your photos! The creative results are placed on broncolor's Gen NEXT Blog online and are intended serve as inspiration for a new generation of photographers.

### Gen NEXT Project

broncolor not only offers young pros the opportunity for professional development, but also the chance to shape the future of photography.



CRISTINA OTERO GONZAGA MANSO YULIA GORBACHENKO LAURI LAUKKANEN ANITA ANTI



WONG DUSTIN SNIPES JASON JIA MANUEL MITTELPUNKT

Watch the next generation light the way



Meet our 2nd Generation of winners



GEN  
NEXT

Gen NEXT is a project which enriches both sides – young, professional photographers get fabulous equipment which will accompany them throughout their careers and, in exchange, broncolor gains fascinating insights into their ground-breaking photography and can thus adapt their products to meet the next generation's photography and video needs.

In an annual online competition, broncolor looks for the hottest talents from all genres of photography worldwide. In working with young photographers, broncolor ensures that it is always at the forefront of the latest photographic trends and remains the premier source for professional lighting equipment – also for the new generation.

<http://gennext.broncolor.com>

creative  
workshop


## broncolor Workshops – 2 Days Pure Creativity

broncolor offers several two-day workshops for the «People» and «Products» sectors; the basic principle is similar for both courses. While the «Products» workshops concentrate on photographing objects, the «People» workshops deal with the subjects full-body, beauty and portrait photography. On the first day the instructor demonstrates and explains the various lighting techniques with the aid of a photo model. The second day is devoted to group work with one model for each group.

In small groups the very intensive exchange of knowledge and experience between the

participants, and mutual inspiration combine to promote a creative atmosphere. The objective of these courses is to introduce the photographers to new possibilities and ideas so that they can react faster, more efficiently and, above all, better to the challenges of their everyday professional lives.

Besides digital small and medium-format cameras, our professional photo studio has the entire range of broncolor flash equipment available. The concept is subject to continual review. You can see the latest versions on our website.






The illumination of the artichoke does show darker areas (almost black) but no shadows. To get a shadowless light, you might want to try a Ringflash which would, however, not work in this situation - the illumination would be very even.

A Picolite with the narrowest grids would be precise enough to light only a very small part of the object, but it would create dominant shadows. So, the Picolite rotates around the artichoke (like a ringflash!) and fires constantly. 10 flashes hit the centre, 20 the periphery. In a dark studio, the camera remains open long enough for all 30 "exposures" to reach the sensor. In this way, the qualities of a Ringflash and a Picolite are combined.

© „how to“ by Urs Recher (broncolor)

The picture is shot with a medium format camera and a focal length of 120 mm. The exposure time was 32 s and the aperture f/32.



## broncolor's HOW TO – Learning with broncolor was never easier



„How To“ explains very simply the numerous possibilities and applications of broncolor light modifiers. In each case the concept consists of a beautiful picture, the lighting set-up, visualised with a graphic diagram, the camera settings, and an explanation of the exposure.

All the examples can be called up on our website under “How To”. You can either let yourself be inspired by the examples or, very specifically, search for examples with the appropriate light modifier. Several of the “How To” examples have been filmed to give

an even more detailed insight into how that particular image was created. The videos can be called up on the website, or on our Youtube channel.

broncolor publishes new examples at frequent intervals. Follow us on social media, such as Facebook or Twitter; you will then be notified automatically when a new example is available.

<http://www.bron.ch/broncolor/how-to>





## Compatibility, getting started, expansion

The broncolor modular system includes monolights, power packs, lamps and accessories, which are mutually compatible. This facilitates the start with the broncolor system, as you always will be able to enlarge it step by step and adopt it to your individual requirements. Combination with earlier broncolor equipment is virtually unrestricted.

### The broncolor system

Output, easy to handle, microprocessor control system, and quick flash series – no matter what criterion makes you buy a flash system. Amongst the broncolor system you will find the units completely in line with your lighting requirements. They let you advance into new applications and succeed with motion shots. Various lamps and a wide selection of reflectors, area lights and accessories give you ample latitude in your visions of lighting and creativity.

### Warranty

All broncolor equipment is characterised by high quality standards. All equipment – with the exception of flash tubes, modelling lamps, rechargeable batteries, textiles and parts subject to wear – carry a 2-year warranty.

### Ordering power supplies

broncolor equipment can be supplied for various voltages and frequencies. Please replace the last two digits “XX” of the item number by the code number for your rated voltage.

Power supply	Code
100 V 50 Hz	.01
100 V 60 Hz	.02
110 V 50 Hz	.03
110 V 60 Hz	.04
115 V 50 Hz	.05
115 V 60 Hz	.06
117 V 60 Hz	.07
120 V 60 Hz	.08
220 V 50 Hz	.10
230 V 50 Hz	.11
240 V 50 Hz	.12
240 V 60 Hz	.13
220 V 60 Hz	.14
200 V 50 Hz	.15
200 V 60 Hz	.16

### Special brochures

Please ask your broncolor representative for detailed special brochures relating to individual broncolor products and services.

**A multitude of successful photographers is internationally active and makes demands, at the different shooting locations, to rent a broncolor flashlight system, quickly and without complications. And also, often in combination with a professional rental studio.**

Bron Elektronik AG offers, in cooperation with its distributors in the various countries, an international rental service, broncolor worldlight. This network precisely meets those requirements. broncolor flashlight systems can be rented in 34 countries in more than 120 rental locations. In certain countries you also have the possibility of renting a broncolor equipped studio.

**broncolor worldlight offers you:**

- the possibility to rent the desired broncolor flashlight equipment, quickly and without complications

- to temporarily expand your own flashlight equipment, at short notice – for example for a complex shoot
- to use special effect lamps and light shapers for demanding light effects
- to test broncolor equipment before purchasing
- always the latest and state-of-the-art flash equipment

For further information, please contact your local broncolor dealer or us, directly.

A country specific list of our rental studios is available on our website under:

**worldlight**  
RENT A SYSTEM BY **broncolor**

[www.broncolor.com](http://www.broncolor.com)  
> Buy/Rent





Bron Elektronik AG  
CH-4123 Allschwil / Switzerland  
[www.bron.ch](http://www.bron.ch)

**D0163.03**

We reserve the right to make changes due to technical developments. broncolor, kobold and bron are registered trademarks.  
©2015 by Bron Elektronik AG Allschwil. All rights reserved. All images and their copyrights owned by the photographers.  
Reprinting and reusing without the permission of the photographer prohibited. Printed in Italy 07/15

 Photographer: Dustin Snipes, USA